

MARISOLV® 9000

TECHNICAL DATA SHEET
Date: 15.10.2021 – Version 21

Solvent / Diluent

Product Description

MARISOLV® 9000 is a solvent / diluent for use with MARISEAL® SYSTEM liquid-applied waterproofing membranes.

Advantages

- Excellent compatibility with single component polyurethane liquid-applied waterproofing membranes and coatings
- Excellent solubility
- Suitable for use both for hand application and airless spray application

Main Uses

MARISOLV® 9000 is used as a solvent / diluent in combination with MARISEAL® 250/260/270/etc. liquid-applied waterproofing membranes.

Application

Add MARISOLV® 9000 into MARISEAL® 250/260/270/etc. liquid-applied waterproofing membrane, and mix with a low speed electrical mixer, for 2-3min, at a ratio of 4 to 8% by weight. For detailed application instructions, contact our R+D department.

Safety Measures

MARISOLV® 9000 contains xylene. Flammable. See information supplied by the manufacturer. Please study the Safety Data Sheet.

PROFESSIONAL USE ONLY

Our technical advice for use, whether verbal or written, is given in good faith and reflect the current level of knowledge and experience with our products. When using our products, a detailed object-related and qualified inspection is required in each individual case in order to determine whether the product and /or application technology in question meets the specific requirements and purposes. We may guarantee only that our products are compliant with their technical specification; correct application of our products therefore falls entirely within your scope of liability and Users are responsible, in any case, for complying with local legislation and for obtaining any required approvals or authorizations, when necessary, either for their purchase and/or for their use. Values in this technical data sheet are given as examples and may not be regarded as specifications. For product specifications contact our R+D department. The new edition of the technical data sheet supersedes the previous technical information and renders it invalid. It is therefore necessary that you always have to hand the current code of practice.

CONSTRUCTION

